



INDICUS DRAPER is a water-based acrylic emulsion suitable for interior walls. It provides smooth matt finish and excellent hiding. Its anti-peel technology delivers best-in-class resistance against peeling and keeps the wall new for a longer time compared to cement paints*.



Anti-peel technology
that keeps your wall new for a longer time*



Higher coverage*



3 years performance warranty**

Features

- Smooth finish
- Excellent hiding
- Deeper shades

Technical Properties

Bases	D-3, D-22
Vehicle Type	Acrylic
Specific Gravity	1.42 ± 0.02
Viscosity @ 27°C	100 KU ± 2
VOC Level	<20 g/L
Drying Time ¹	Surface Dry : 30 to 40 mins. Recoat : 4 to 6 hours
Dilution	Up to 50% with clean water

¹ Drying time will vary depending upon the surface condition, degree of dilution and method of application.

* On tested conditions.

** Conditions apply. Please refer INDICUS DRAPER Warranty Guide for conditions and information on the warranty available at www.indicus.co.in/warranty.



Finish



MATT



GLOSS



SILK



SATIN

Coverage

Approximately **265 sq.ft.** per litre per coat

Coverage is dependent on the degree of dilution, surface condition and method of application.

Application Procedure

Surface Preparation

1. New masonry surfaces must be properly cured and sound in condition.
2. Ensure the surface is clean, dry and free from seepage, leakage, old paint, dirt, dust and any loose particles.
3. Any growth of fungus, algae or moss needs to be removed thoroughly with wire brush and water.
4. In case of dampness/waterproofing problems, repair the surface using GODRY Waterproofing Solutions.
5. Open non-structural cracks in V-groove and fill with INDICUS EASYSEAL.

Application

1. Prime the surface using INDICUS ULTRAPRIME as per the recommended application procedure.
2. Apply INDICUS ULTRACOAT Wall Putty as per the recommended method to smoothen and level the surface.
3. Apply another coat of INDICUS ULTRAPRIME and allow it to dry.
4. Apply 2-3 coats of DRAPER after diluting it with clean water by up to 50%. A gap of 4 to 6 hours should be given between the coats.

Post Painting Care

- Prevent any damage to the paint film by sharp objects.
- For best performance of the paint, clean the surface of all algal and fungal growth, if any, at regular intervals of six months.

Precautions

- Diluted paint must be used within 24 hours of dilution.
- Do not over-thin or over-extend the brush.
- In coastal areas, it is recommended to apply the topcoat immediately after the undercoat is dry.
- Close container after each use and store in a cool and dry place.

Health & Safety

- No added Lead, Mercury, Chromium, Arsenic or other heavy metals.
- Allow adequate ventilation during application and drying.
- Do not breathe spray mist or sanding dust.
- Use rubber gloves, dust mask or nose pad during application, sanding and clean up.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Do not pour leftover paint/primer down the drain or in water courses.

Packaging

INDICUS DRAPER is available in 1, 4, 10 & 20 Litre packaging.

Shelf Life & Storage

Shelf life is 36 months from the date of manufacturing, if stored in unopened and original packaging. Store in cool & dry place away from direct sunlight.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied guaranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.