

Indicus[®]
AQUASEAL

Waterproof

Superior coating for your house!



**Protection.
Edge to edge.**



Reinforced
with fibres



3 years
waterproofing
warranty*



For exterior
use



INDICUS® AQUASEAL® is an acrylic waterproof coating for all types of cementitious surfaces in exterior areas. It forms a durable and elastic membrane that provides excellent water resistance. The specially added polyester fibres deliver excellent mechanical properties and adhesion.



Reinforced with fibres
for superior mechanical properties



Flexible



3 years waterproofing warranty*



Durable



Crack bridging



Anti-algal



Efflorescence resistant

Technical Properties

Colour	White
Specific Gravity	1.36 ± 0.05
Viscosity @ 27 °C	120 KU ± 5
Tensile Strength	>2.5 N/mm ²
Application Temperature	5 °C to 35 °C
VOC Level	<20 g/L
Drying Time ¹	Surface Dry : 30 to 40 mins. Recoat : 4 to 6 hours

¹Drying time and coverage will vary depending upon the surface condition, degree of dilution and method of application.

Coverage

- On horizontal surface, approx. 10 sq.ft./L for 3 coats.
- On vertical surface, approx. 25 sq.ft./L for 2 coats.

Coverage is dependent on the degree of dilution, surface condition and method of application.

Application Procedure

1. Clean the surface thoroughly and repair the damages, if any, using polymer modified repair mortar.
2. New cementitious surfaces should be allowed to cure for minimum of 28 days before coating.

On Horizontal Surface

1. Apply one self-priming coat by diluting AQUASEAL with 30% clean water on the surface and allow it to dry.
2. Apply one undiluted coat of AQUASEAL and allow it to dry.
3. Apply the second undiluted coat of AQUASEAL perpendicular to the first coat.

On Vertical Surface

1. Apply one self-priming coat by diluting AQUASEAL with 10% water on the surface and allow it to dry.
2. Apply one undiluted coat of AQUASEAL and once dried, complete with top coat.

Cautions

- Do not stir in high speed
- Do not apply in direct sunlight or during rains
- Ambient temperature and material temperature should be between 10 to 40°C
- Ensure parapet walls, outlets, protrusions and corners are properly coated to achieve full waterproofing.
- The coating is not designed for heavy foot traffic

Packaging

INDICUS AQUASEAL is available in 1, 4, 10 & 20 Litre packaging.

Shelf Life & Storage

Shelf life is 36 months from the date of manufacturing, if stored in unopened and original packaging. Store in dry place away from direct sunlight.

For more information, please visit www.indicus.in



* Conditions apply. Please refer INDICUS AQUASEAL Warranty Guide for conditions and information on the warranty available at www.indicus.in/warranty.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied guaranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.