

CEILING BRIGHT[®]

Bright Emulsion For Ceilings



Indicus[®]

INDICUS CEILING BRIGHT is a water-based acrylic emulsion formulated specifically for ceilings. Its super bright white colour creates a spacious feel and maximises ambient light in the room.



Super bright
white



Creates spacious feel



Excellent opacity



For interior use

Technical Properties

| | |
|--------------------------|---|
| Colour | Bright white |
| Vehicle Type | Acrylic |
| Specific Gravity | 1.40 ± 0.02 |
| Viscosity @ 27°C | 100 KU ± 2 |
| VOC Level | <20 g/L |
| Drying Time ¹ | Surface Dry : 30 to 40 mins. Recoat : 4 to 6 hours |
| Dilution | Up to 50% with clean water |

¹ Drying time will vary depending upon the surface condition, degree of dilution and method of application.

Packaging

INDICUS CEILING BRIGHT is available in 4, 10 & 20 Litre packaging.



Finish



MATT



GLOSS



SILK



SATIN

Coverage

Approximately 220 sq.ft. per litre per coat

Coverage is dependent on the degree of dilution, surface condition and method of application.

Application Procedure

Surface Preparation

1. New masonry surfaces must be properly cured and sound in condition.
2. Ensure the surface is clean, dry and free from seepage, leakage, old paint, dirt, dust and any loose particles.
3. Any growth of fungus, algae or moss needs to be removed thoroughly with wire brush and water.
4. In case of dampness/waterproofing problems, repair the surface using GODRY Waterproofing Solutions.
5. Open non-structural cracks in V-groove and fill with INDICUS EASYSEAL.

Application

1. Prime the surface using INDICUS ULTRAPRIME as per the recommended application method.
2. Apply INDICUS ULTRACOAT wall putty as per the recommended method to smoothen and level the surface.
3. Apply another coat of INDICUS ULTRAPRIME and allow it to dry.
4. Apply 2-3 coats of CEILING BRIGHT after diluting it with clean water by up to 50%. A gap of 4 to 6 hours should be given between the coats.

Precautions

- Diluted paint must be used within 24 hours of dilution.
- Do not over-thin or over-extend the brush.
- In coastal areas, it is recommended to apply the topcoat immediately after the undercoat is dry.
- Close container after each use and store in a cool and dry place.

Health & Safety

- No added Lead, Mercury, Chromium, Arsenic or other heavy metals.
- Allow adequate ventilation during application and drying.
- Do not breathe spray mist or sanding dust.
- Use rubber gloves, dust mask or nose pad during application, sanding and clean up.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Do not pour leftover paint/primer down the drain or in water courses.

Shelf Life & Storage

Shelf life is 36 months from the date of manufacturing, if stored in unopened and original packaging. Store in cool & dry place away from direct sunlight.

Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied guaranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.