



**Beauty all around.**



**Weather  
resistant**



**Attractive  
glossy finish**



**Solvent  
thinnable**



INDICUS® GLAZ® is a solvent-based premium enamel that gives a mirror like gloss finish to the painted surface. Its durable film protects the surface against weather conditions and is resistant to household stains.



#### Weather resistant

Highly resistant to variable atmospheric conditions.



#### High durability

Tough film resistant to mechanical damage.



#### Attractive glossy finish

Gives a mirror like gloss finish that's stable over time.



#### Stain resistant

Highly washable surface that gives the ability to remove stains.

### Working Properties

Finish	High gloss
Method of Application	Brush, felt roller or spray
Application	Between 10 to 40 °C, humidity below 70%
Drying Time*	Surface Dry : <1 hour Tack free : 3 hours
Drying Time To Recoat*	6-8 hours
Dilution With	Mineral Turpentine Oil (MTO)
Dilution	10-15% by volume

\* Drying time and coverage will vary depending upon the surface & climatic condition, degree of dilution and method of application.

### Areas of Application

INDICUS GLAZ can be used:

- on suitably prepared steel, wooden and masonry surfaces
- In both interior and exterior areas

### Coverage

Approximately 200 sq.ft. per litre per coat.

Coverage is dependent on the degree of dilution, surface condition and method of application.

### Application Procedure

1. Ensure the surface is clean and free from any adhesion inhibiting compounds.
2. Blast the surface or sand with emery paper and wipe clean.
3. Apply one coat of appropriate primer and allow it to dry for 6 to 8 hours.
4. Use oil-based putty to fill cracks and dents, if any, to make the surface uniform.
5. After sanding the puttied surface, apply another coat of primer and allow it to dry overnight.
6. Sand the primed surface lightly and wipe clean.
7. Apply two coats of GLAZ to get a rich, smooth, and high-gloss finish giving 6 to 8 hours gap between the coats.

### Healthy & Safety

- No added Lead, Mercury, Chromium, Arsenic or other heavy metals.
- Store container in upright position with lid tightly closed in a cool and dry place, away from any ignition sources.
- Keep out of reach of children and away from any combustible materials, food, drinks, etc.
- Do not pour leftover primer down the drain or in water courses.
- Highly toxic to aquatic organisms and may cause long term adverse effect to aquatic environment.
- In case of spills, contain using sand or earth.

### Shelf Life & Storage

Shelf life is 36 months from the date of manufacturing, if stored in unopened and original packaging. Store in dry place away from direct sunlight.

For more information, please visit [www.indicus.in](http://www.indicus.in)



Disclaimer: The product information and applications details given in this data sheet is meant to serve as a general guideline only. Users are advised to undertake a trial for product suitability prior to full-scale usage. There is no express or implied guaranty/warranty for the results. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.